

**V-Twin Mfg.
Oil Drain Spigot Tool
Fits 2009-Up FLT Models
VT Part No. 16-0096**

This tool should only be used by a knowledgeable and trained motorcycle technician. V-Twin Mfg. Accepts no responsibility for improper use.

Installation Instructions:

1. Using the 5/8" socket and ratchet, loosen the drain plug which is located on the bottom of the oil pan.
2. Insert the oil drain adapter through the hole in the crossover plate on the bottom of the frame and place it over the drain plug.
3. Rotate the adapter counter-clockwise to engage the shoulder on the side of the adapter with the lip of the crossover plate on the bottom of the frame.
4. Be sure it is locked into place and that you have an even seal around the top of the oil drain adapter and the oil pan.
5. Remove the drain plug with the 1/4" allen socket and ratchet. An extension may be needed.
6. Allow the oil to drain through the center of the oil drain adapter and into the drain pan.
7. Remove drain plug from the oil drain adapter and installed a new o-ring on the drain plug.
8. Re-insert the drain plug into the oil drain adapter and insert it into the oil pan and tighten finger tight.
9. Remove the oil drain adapter.
10. Tighten the drain plug to 14-21 ft-lbs.
11. Refill oil tank according to the instructions listed in the service manual.

