



## INSTRUCTION SHEET FOR #2244

### 35MM HEX TOP FORK NUT SOCKET 3/8" DRIVE

USE ON BIG TWIN 1948-PRESENT (WIDE GLIDE FORKS)

USE ON SPORTSTER 1988-PRESENT



Refer to H.D.® Service Manual for specifications.

1. Remove fork caps with fork nut socket by turning nut counter clockwise.
2. Use caution as fork caps are under pressure from fork springs on some models.

CAUTION: WEAR SAFETY GLASSES. EXCESSIVE FORCE MAY DAMAGE PARTS! SEE JIMS® CATALOG FOR OVER 100 OTHER TOP QUALITY PROFESSIONAL TOOLS. THE LAST TOOLS YOU WILL EVER NEED TO BUY.

*"From the Track... To the Street!"*

555 DAWSON DRIVE, CAMARILLO, CA 93012 PHONE 805-482-6913 • FAX 805-482-7422



## INSTRUCTION SHEET FOR #2244

### 35MM HEX TOP FORK NUT SOCKET 3/8" DRIVE

USE ON BIG TWIN 1948-PRESENT (WIDE GLIDE FORKS)

USE ON SPORTSTER 1988-PRESENT



Refer to H.D.® Service Manual for specifications.

1. Remove fork caps with fork nut socket by turning nut counter clockwise.
2. Use caution as fork caps are under pressure from fork springs on some models.

CAUTION: WEAR SAFETY GLASSES. EXCESSIVE FORCE MAY DAMAGE PARTS! SEE JIMS® CATALOG FOR OVER 100 OTHER TOP QUALITY PROFESSIONAL TOOLS. THE LAST TOOLS YOU WILL EVER NEED TO BUY.

*"From the Track... To the Street!"*

555 DAWSON DRIVE, CAMARILLO, CA 93012 PHONE 805-482-6913 • FAX 805-482-7422