

VT No. 24-1180

The rider's safety depends upon the correct installation of this kit. Use the appropriate service manual procedures. If the procedure is not within your capabilities or you do not have the correct tools, have a dealer perform the installation. Improper installation of this kit could result in death or serious injury

NOTE

This instruction sheet references service manual information. A service manual for your model motorcycle is required for this installation.

Kit Contents

See Figure 1. and Table 1.

REMOVAL

1. See the service manual and follow the front fork removal procedures.
2. Remove the two OE fork cover screws. Save screws for installation.
3. Slide the fork cover off the front forks.

INSTALLATION

See Figure 1. The Fork Slider Covers included in this kit install in the same manner as the original equipment parts. Refer to the service manual for proper installation procedures.

1. Apply Loctite 243 to threads of screws.
2. Install the new fork slider cover and two screws on the front fork . Tighten to 24-48 in-lb.
3. Follow the installation instructions to install and adjust the front forks.

NOTES

- Verify that there is no contact made between the slider covers and the fender when the suspension is fully compressed.
- For models with a chrome skirt, verify there is clearance between skirt and new fork covers.




Figure 1.

Figure 1. Service Parts: Upper Fork Slider Covers (Edge Cut Shown)

Table 1. Service Parts

Item	Description (Quantity)
1	Fork slider covers, chrome (2)
	Fork slider covers, Edge Cut (2)