

V-Twin Mfg.
COMPLETE WIRING HARNESS KIT
For 1936-1937 BT, 45" (EXCEPT VL)
VT No. 32-0701

This is a custom application and rider safety depends on proper installation. This product should only be installed by a knowledgeable and trained motorcycle technician. V-Twin Mfg. accepts no responsibility for improper installation.

| | |
|----------|---|
| 1613-30A | Circuit breaker to coil wire, Black 25" |
| 1742-36 | Switch to generator and relay cable, (2 Wires) Red 40" and Green 30" |
| - | Switch to ammeter wire, Red 10" |
| 4701-37 | Switch to coil, tail lamp & battery positive junction terminal cable: Red, Green & Black 29" |
| 4702-36 | Headlamp to handlebar toggle switch cable: Red/Black Tracer 27"; Red/Yellow Tracer 28" Black/Red Tracer 28" |
| 4703-36 | Switch to horn and toggle switch cable: (2 Wires) Red & Green 26" |
| 4704-34 | Tail lamp wire: Black 52" |
| 4706-36 | Battery Negative ground wire: Black 9" |
| 4706-39 | Battery positive wire: Red 9" |
| 4706-39 | Generator to relay wire: Red 9", wire is correct length for side valve models. When applied to OHV models, shorten to 5 1/2" and attach enclosed terminal |
| 4710-36 | Horn switch wire: Black 28" |
| 4712-36 | Panel bulb contact wire: Black 5" with one terminal attached |

