

**Andrews Twin Cam Gear Drive Cams
for 1999-2006 Twin Cams Except 2006 FXD**

Duration							
Part#	Grind	Timing*	.053	.020	Valve Lift	Lift @ TDC	Springs
10-8159	12G	02/34 40/02	216 222	252 259	.489 .489	.091 .095	Stock
10-8130	21G	10/30 40/08	220 222	255 264	.498 .498	.134 .121	Stock
10-8131	26G	11/35 41/09	226 230	262 266	.490 .490	.138 .120	Stock
10-8142	31G	10/46 52/08	236 240	272 276	.510 .510	.131 .120	Stock
10-8191	32G	10/46 52/08	236 240	272 276	.570 .570	.131 .120	Hi-Lift
10-8132	37G	18/38 46/14	236 240	272 276	.510 .510	.174 .148	Stock
10-8210	54G	16/42 43/15	238 238	273 273	.555 .555	.165 .158	Stock
10-8134	50G	20/48 54/18	248 252	283 287	.510 .510	.184 .168	Stock
10-8135	55G	22/46 52/20	248 252	283 292	.550 .550	.197 .181	Hi-Lift
10-8136	60G	24/56 58/22	260 260	296 296	.560 .560	.205 .192	Hi-Lift
10-8149	67G	24/48 58/22	252 260	287 297	.570 .570	.209 .187	Hi-Lift
10-8152	59G	29/57 63/27	266 270	303 307	.590 .590	.238 .218	Hi-Lift
10-8153	64G	30/62 66/30	272 276	307 312	.640 .640	.262 .232	Hi-Lift

*Timing and duration listed for .053 cam lift