



Cam Shaft



Jims Camshaft/Crankshaft Locking Tool will lock the gear teeth on the TC 88 model engine. Instructions included.
VT No. 16-0790



Jims Cam Chain Tensioner Unloader will hold the tension of the primary cam chain on the TC 88 model engine. Instruction included.
VT No. 16-0793



Jims Camshaft Remover and Installer Tool allows removal and installation of cams in the TC-88 model engine. Tool is used in conjunction with VT No. 16-0793 cam chain tensioner unloader.
VT No. 16-0792



Jims TC-88 Camshaft Bearing Tool designed to remove and replace the right crankcase bearing in and out with no damage to crankcase.
VT No. 16-1275



Jims TC-88 Inner Cam Installer positions the two inner cam needle bearings and perfectly aligns to the shaft bores for a precision press fit.
VT No. 16-1278



Jims TC-88 Cam Bearing Puller used to remove bearing from camshaft, this tool is designed to remove the bearing straight with no slipping or binding. Use on all TC-88.
VT No. 16-1280



Jims TC-88 Inner Cam Bearing Remover replaces inner bearing easily without damage to crankcase and also prevents rollers from falling into crankcase. Use on TC-88.

VT No. 16-1279



Jims Outer Balancer Bearing Installer and Remover Tool. This tool removes and installs the outboard balancer bearing on 96" and 110" "B" Softtail engines 2007-up.
VT No. 16-0324



Jims Cam Assembly Tool for all 2006-up Dyna and 2007-up FXST, FLT models. Used to hold both cams in an upright position while lowering the cam support plate over cam journal.
VT No. 16-0323



Jims TC-88 Crankshaft Guide use to spread pinion bearing rollers while reassembling right side engine case on to flywheel assembly.
VT No. 16-1281

Cam Tool



Tune-A-Cam Kit includes easy to read degree wheel dial indicator, T.D.C. locator, lightweight checking springs and packed in a plastic case. Also checks cam or crank end play, shaft and gear run out.

VT No. 16-0970



Delkron Space-N-Time Tool attaches to pinion shaft of 1970-up BT, allowing you to set cam end play, check gear lash, breather timing, valve timing, and 12 other checks for blue print quality engine building. Instructions included.

VT No. 16-0714



S&S Degree Wheel Kit designed to fit the sprocket shaft of any Big Twin or XL model. Each kit also comes with pointer that is held in place by center crankcase bolt.

VT No. 16-0909



Crane Cams Installation Tool comes with easy instructions for the mechanic to install Crane's adjustable pushrods without removing the gas tank or rocker covers. In all FL-FX with adjustable pushrods, the tool makes it easy for cam changes. No removal of pushrods, pushrod covers, tappets or tappet guides. Tappets never have to fall out of the guides while doing cam changes.


VT No. 16-0030



48-0470 Knuckle Head



48-0030 1340 cc



48-0033 Dual Cam



48-0025 Panhead



48-0044 Shovelhead



48-0044 Shovelhead

Motor Plaques measure 18" x 24" and are made of metal.