

V-Twin Mfg.
Kreem Gas Tank Prep Cleaner and Conditioner
VT Part No. 41-0112

This is a custom application and rider safety depends on proper installation. This product should only be installed by a knowledgeable and trained motorcycle technician. V-Twin Mfg. accepts no responsibility for improper installation.

Installation Instructions:

1. Read warning statements on this label and on Part B label.
2. Remove the tank from the vehicle, remove any valves and petcocks and stop all outlets.
3. Wash out tank with hot soapy water. If the tank is badly rusted and has loose flaky rust add stones or nuts and bolts to agitate to remove loose rust.
4. For new tanks, it is important to remove oily protective coating before using Tank Prep. An industrial strength detergent or commercial degreaser/cleaner like KREEM's New Tank Cleaner/Degreaser or acetone should be used.
5. Pour Tank Prep A into tank and add 5 gallons of warm water. Tank Prep A works best when tank is completely full and in contact with all metal surfaces. If this is not possible you should turn the tank to different positions so that the solution has extended contact with all metal surfaces.
6. Leave Tank Prep A in the tank until all the rust is dissolved and the metal is etched to a dull gray finish. The time required will depend on the amount of rust in the tank. New tanks can be etched in 4 hours. Rusty tanks will take longer; we suggest overnight.

ALLOW TANK TO VENT. DO NOT ALLOW PRESSURE TO BUILD UP!

7. Drain Tank Prep A solution into a plastic container and check tank. If all rust is removed proceed to step B. If rust is still present add saved Tank Prep A solution to tank again until rust is removed.
8. Flush the tank with clean water until rinse water no longer foams and all traces of Tank Prep are removed. Remove all excess water.
9. Immediately rinse tank interior with full-strength Tank Prep B and agitate to ensure thorough treatment. Drain out all excess Tank Prep B.
10. Immediately seal the tank with KREEM FUEL TANK LINER according to label directions.

Quantity Required:

Tank Prep-A - Concentrated! Makes 2-1/2 Gallons

Caution:

Tank Prep-A

Before using, user shall determine the suitability of the product for intended use, and user assumes all risk and liability whatsoever in connection herewith. The foregoing may not be altered except by an agreement signed by the offices of seller and manufacturer – KREEM PRODUCTS

WARNING: DANGER-MAY CAUSE BURNS – HARMFUL IF SWALLOWED

Contains phosphoric acid. Avoid contact with skin, eyes and mucous membranes. In case of contact, flush with cool water. For eyes, get prompt medical attention. If swallowed, give 1 or 2 glasses of water and call physician immediately.

KEEP OUT OF REACH OF CHILDREN

Tank Prep-B

WARNING STATEMENT: DANGER! FLAMMABLE!

CONTAINS METHYL ETHYL KETONE

Tank Prep-B solution will damage paint.

USE WITH ADEQUATE VENTILATION - DO NOT BREATHE VAPORS

Avoid contact with eyes. Keep from heat, sparks or flame. Do not smoke; extinguish all flames and pilot lights and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Avoid prolonged contact with skin or prolonged breathing of vapors.

FIRST AID: In case of eye contact, flush thoroughly with water. If irritation persists, get medical attention. If swallowed do not induce vomiting. Get medical attention. If vomiting occurs spontaneously, keep victim's head below his hips to prevent his breathing the vomit into his lungs.

KEEP OUT OF REACH OF CHILDREN.