

SISSY BAR SIDE PLATE KIT VT No. 50-0800

Models

This kit fits 1997 through 1999 FLSTS, and 1984 through 1999 FXSTC, FXSTS, FXSTB, and FXST models.

Additional Parts Required

This kit must be installed with one of several applicable sissy bars.

Warning

The rider's safety depends upon the correct installation of this kit. Use the appropriate service manual procedures. Improper installation of this kit could result in death or serious injury

NOTE

This instruction sheet references Service Manual information. A Service Manual for your model motorcycle is required for this installation.

INSTALLATION

1984 through 1986 FXST

1. Remove the four bolts and associated hardware that secure the fender to the fender brace.

NOTE

Retain original hardware and mark in some manner for later assembly.

2. With sissy bar attached to sideplates, position sideplates on outside of fender braces.

3. Insert bolts supplied with kit from the inside of the fender out through the sideplate and fender brace at rear most fender location. Secure with original lockwashers and acorn nuts. Tighten nuts to 19 ft-lbs.

4. Use longer original bolts to secure sideplates at forward location on rear fender. Secure with original lockwashers and acorn nuts. Tighten nuts to 19 ft-lbs.

1987 and later FXST

NOTE

The bolts included in kit are not required for this installation.

1. Remove four acorn nuts from bolts that secure fender brace to fender.

2. With sissy bar attached to sideplates, position sideplates on outside of fender braces.

3. Secure sideplates onto bolts using the four acorn nuts removed in Step 1.

Tighten nuts to 19 ft-lbs.

FLSTS

NOTE

For installing this kit on FLSTS models, the following hardware parts have been included:

- (2) Spacers
- (4) Flat washers
- (4) 5/16-18 Locknuts
- (2) 3/8-16 Locknuts

1. Remove the acorn nuts and washers that attach the lower saddlebag bracket to the passenger footpeg bracket.

2. Remove the two nuts inside each saddlebag that attach the bag to the motorcycle, and remove both bags. Discard the nuts.

3. Remove the acorn nuts on each side of the fender brace (two on each side).

4. Remove the saddlebag studs (two on each side) and discard the locknuts that hold the forward two studs in place. Save all the hardware for reinstalling the studs.

5. Reinstall rear studs using the two spacers included in this kit and the original bracket nuts saved from Step 4.

Make sure the spacer is located between the fender brace and the hex nut of the stud.

6. With sissy bar attached to sideplates, position sideplates on outside of fender braces.

7. Attach sideplates to fender brace by installing the front saddlebag studs (in the front sideplate holes) with the 3/8 16 locknuts included in this kit, and installing the rear acorn nuts (in the rear sideplate holes). Tighten nuts to 19 ft-lbs.

8. Place flat washers (included in this kit) over each stud.

9. Reinstall saddlebags using 5/16-18 locknuts (included in this kit). Tighten locknuts securely.

10. Reinstall remaining two acorn nuts that secure fender brace to fender. Tighten nuts to 19 ft-lbs.