

FLAMES FRONT FENDER SKIRT

GENERAL

Kit Number

60179-06

Models

These kits are designed for the front fenders on the following models:

- 1980 and later Touring
- 1986 and later FLSTC
- 1993-1996 FLSTN
- 2006 and later FLST

This kit is **not** designed for FLSTF model vehicles.

Kit Contents

Table 1. Kit Contents

Description	Quantity
Fender skirt	1
Screw, pan head	6
Locknut, hex	6
Washer, flat	6
Adhesive foam strip (Heritage models only)	1

INSTALLATION

1. See Figure 1. Remove fasteners (2) from stock fender skirt.

WARNING

Do not contact tire with drill bit when drilling fender holes. Drill bit contact with tire can lead to premature tire failure, which could result in death or serious injury. (00403f)

NOTE

Some early models have rivets for fasteners. These rivets will need to be drilled out. Drill the rivet heads to a sufficient depth to remove the head from the rivet shaft. Do not attempt to drill the rivet all the way through. This may scratch the fender's painted surface.

CLEAN FENDER INSTALLATION




Figure 2. Clean Front Fender Skirt Installation

To install fender skirts on Harley-Davidson Genuine Motor Accessory Clean Fender (Part Number 59054- 96), or FLTR and FLHRS models with clean fenders:




Figure 1. Front Fender Skirt and Assembling Hardware

2. Remove stock fender skirt (1).
3. Thoroughly clean the fender under the skirt. At this point it may be a good idea to wax this portion of the fender to prevent rust in the future.
4. Cut the adhesive foam strip (5) into three equal parts. Remove the backing from the adhesive strips and apply adhesive on middle and two sides at the inside/bottom of the skirt. The foam strips will prevent rattling and unwanted noise.

NOTE

On some FLT models, there may not be enough fender skirt support to allow the application of adhesive strips. If this is true for your motorcycle, you may install this kit without the adhesive strips.

5. Place the fender skirt in position, aligning fastener holes.
6. Install the screws (2) from the outside of the fender. Install the washers (4) and nuts (3) inside the fender.

1. See Figure 2. Clean fender where fender skirt will be mounted (1) and cover that portion of fender with masking tape to protect painted surface during positioning of skirt and drilling of mounting holes.
2. Place fender skirt in desired location and mark mounting hole locations with felt tip pen. The lower edge of the fender skirt should be approximately level, but slightly lower, than the lower edge of the fender.
3. Remove fender skirt and carefully center punch holes at locations marked.

WARNING

Do not contact tire with drill bit when drilling fender holes. Drill bit contact with tire can lead to premature tire failure, which could result in death or serious injury.

4. Drill mounting holes using a 1/8 in. diameter drill bit.
5. Remove masking tape and attach fender skirt as described in **Installation**, steps 3 through 6.