

Performance Cams for 2007-2011 TC-96 and 2006 FXD

| Duration | | | | | | | | |
|----------|-------|------------------|------------|------------|------------|--------------|--------------|---------|
| Part# | Grind | Timing* | CL** | .053 | .020 | Valve Lift | Lift @ TDC | Springs |
| 10-6309 | 09H | -02/28 40/-04 | 105 112 | 206 216 | 242 252 | .492 .486 | .075 .075 | Stock |
| 10-8138 | 21H | 10/30 40/08 | 100 106 | 220 228 | 255 264 | .498 .498 | .134 .121 | Stock |
| 10-8139 | 26H | 11/35 41-09 | 102 106 | 226 230 | 262 266 | .490 .490 | .138 .120 | Stock |
| 10-8143 | 31H | 10/46 52/08 | 108 112 | 236 240 | 272 276 | .510 .510 | .131 .120 | Stock |
| 10-8192 | 32H | 10/46 52/08 | 108 112 | 236 240 | 272 276 | .570 .570 | .131 .120 | Hi-Lift |
| 10-8146 | 37H | 18/38 46/14 | 100 106 | 236 240 | 272 276 | .510 .510 | .174 .148 | Stock |
| 10-6348 | 48H | 13/29 43/15 | 98 104 | 222 238 | 257 273 | .548 .548 | .153 .163 | Stock |
| 10-6354 | 54H | 16/42 43/15 | 103 104 | 238 238 | 273 273 | .555 .555 | .165 .158 | Stock |
| 10-8148 | 50H | 20/48 54/18 | 104 108 | 248 252 | 283 287 | .510 .510 | .184 .168 | Stock |
| 10-8156 | 55H | 22/46 52/20 | 102 106 | 248 252 | 283 292 | .550 .550 | .197 .181 | Stock |
| 10-8157 | 60H | 24/56 58/22 | 106 108 | 260 260 | 296 296 | .560 .560 | .205 .192 | Hi-Lift |
| | | | | | | | | |

*Timing and duration listed for .053 cam lift

** Lobe Center line angle