

Andrews Shovelhead and Panhead Camshafts

Part#	Grind	Timing*	Duration		Valve Lift		Lift @ TDC**	Springs
			.053	.020	Shovel	Pan		
10-2011	J	21/41	242	292	.405	.425	.154	Stock
10-2020		41/21	242	292	.405	.425	.154	
10-2030								
10-2260	A2	19/43	262	280	.450	.470	.156	Stock
10-2263		50/18	248	290	.450	.470	.142	
10-2267								
10-2310	1	16/36	232	288	.427	.450	.136	Stock
10-2140		36/16	232	288	.427	.450	.136	
10-2150								
10-2340	2	15/35	230	288	.490	.512	.133	Hi-Lift
10-2350		35/15	230	288	.490	.512	.133	
10-2351	B2	26/50	256	295	.485	.507	.187	Hi-Lift
10-2353		53/25	258	296	.485	.507	.176	
10-2358								
10-2420	BH	24/52	256	302	.450	.470	.156	Hi-Lift
10-2430		52/24	256	302	.450	.470	.156	
10-2440								
10-2510	7	29/53	262	303	.510	.535	.206	Hi-Lift
10-2265		59/27	266	325	.510	.535	.186	
10-2266								
10-2600	C	37/61	278	318	.525	.550	.234	Hi-Lift
10-2610		61/37	278	318	.525	.550	.234	
10-2620								

* Timing listed at .053 cam lift

**TDC Shovel valve lift listed: TDC Pan valve lift will be 5% higher