

S&S Chain Drive & Gear Drive Cam specifications for 2000-Up TC-88

Part #	Valve Timing open/close		Valve Duration		Valve lift	Centerline		Lift @TDC	
	Intake	Exhaust	Intake	Exhaust		Intake	Exhaust	Intake	Exhaust
10-5182	18°/18°	46°/11°	216°	237°	.509"	90°	107.5°	.174"	.140"
10-5160	20°/38°	52°/20°	238°	252°	.510"	99°	106°	.187"	.178"
10-5177									
10-5246									
10-5266									
10-6551**	17°/19°	41°/17°	216°	238°	.550"	91°	102°	.178"	.170"
10-7551**									
10-9551**									
10-5166	20°/40°	55°/20°	240°	255°	.570"	100°	107.5°	.187"	.179"
10-5178									
10-5247									
10-5267									
10-6570									
10-7570									
10-9570									
10-6583	5°/18°	58°/24°	203°	262°	.583"	96.5°	107°	.113"	.206"
10-7583									
10-9583									
10-5168	20°/45°	60°/20°	245°	260°	.585"	102.5°	110°	.186"	.179"
10-5179									
10-5248									
10-5268									
10-6585									
10-7585									
10-9585									
10-5170	20°/55°	60°/20°	255°	260°	.625"	107.5°	110°	.189"	.184"
10-5180									
10-5249									
10-5269									
10-6625									
10-7625									
10-9625									
10-5172	25°/60°	65°/25°	265°	270°	.640"	107.5°	110°	.228"	.214"
10-5181									
10-5250									
10-5270									
10-6640									
10-7640									
10-9640									
10-7675	25°/64°	70°/25°	269°	275°	.675"	109.5°	112.5°	.235"	.205"
10-9675									

**551 cams are not recommended with compression ratio of 10:1 or higher